

3M Fire Protection Products
3M™ Fire Barrier Tuck-In Wrap Strips

Time & Labor Savings All Wrapped Up

Simplified installation meets labor savings.

The 3M™ Fire Barrier Tuck-In Wrap Strips are designed for use with plastic pipe penetrations through floors and walls (see applicable UL listed systems). In top-side firestop installations, the tuck-in wrap strip simplifies labor by helping to eliminate the need for retaining collars, concrete screws, ladders, etc. The flexible intumescent strip wraps around the pipe and easily slides into the annular space. Follow the wrap strip installation with 3M™ Fire Barrier Sealant CP 25 WB+, IC 15 WB+, or 3000 WT to help complete your installation.



3M™ Fire Barrier Tuck-In Wrap Strips

Features and Benefits

- Engineered for top-side firestop through penetration installations on concrete floors. May also be used in block, concrete, gypsum wall and wood floor assemblies.
- Labor savings—helps eliminate the need for bottom-side installation materials (retaining collar, concrete screws, ladder, etc.).
- Flexible intumescent strip wraps around pipe to fill tough areas and gaps.
- Adhesive closure tab for easy installation. (WS 200, WS 300 and WS 400)
- UL tested and fire-rated up to 3 hours.
- Pre-cut strips in three sizes, plus rolls for larger applications.
- Intumescent material expands up to 100x in volume in the event of a fire, to seal the penetration.
- Roll can be cut to length allowing for top-side installation when firestopping 6-inch plastic pipes through concrete floors, concrete block and gypsum walls.

Applications

3M™ Fire Barrier Tuck-In Wrap Strips are designed for use with PVC, ccPVC, and FRPP plastic pipes penetrating through concrete floors, block and concrete walls, and gypsum stud walls. Wrap strip easily slides into annular space and is topped with 3M™ Fire Barrier Sealant CP 25 WB+, IC 15 WB+, or 3000 WT.

NOTICE: This product is not acceptable for use with chlorinated polyvinylchloride (CPVC) pipes.



Wrap 3M™ Fire Barrier Tuck-In Wrap Strip around pipe, over floor opening, and adhere label to adjacent side of foam strip.



Gently slide wrap strip downward into concrete floor to fill gaps.



Once installed, wrap strip should be seated slightly below concrete floor surface.



Follow wrap installation with layer of 3M™ Fire Barrier Sealant CP 25 WB+, IC 15 WB+, or 3000 WT to create seal that meets code, fire-rated to 3 hours.

Ordering Information

Product	Product Number	Product Thickness	Product Height	Product Length	UPC	Units/Case
3M™ Fire Barrier Tuck-In Wrap Strip	WS 200	3/16 in. (5mm)	2-1/2 in. (64mm)	8-1/4 in. (210mm)	500-51115-18814-0	24 Strips
	WS 300	3/16 in. (5mm)	2-1/2 in. (64mm)	11-1/2 in. (292mm)	500-51115-18815-7	24 Strips
	WS 400	3/16 in. (5mm)	2-1/2 in. (64mm)	14-7/8 in. (378mm)	500-51115-18817-1	24 Strips
	WS Roll	3/16 in. (5mm)	2-1/2 in. (64mm)	8-1/5 ft. (2.5m)	000-51115-18821-3	6 Rolls



3M

Building and Commercial Services Division

3M Center
Building 223-2N-21
St. Paul, MN 55144-1000
1-800-328-1687
www.3M.com/firestop



FILL, VOID OR CAVITY MATERIAL
FOR USE IN THROUGH-PENETRATION
FIRESTOP SYSTEMS
SEE UL FIRE RESISTANCE DIRECTORY
90G9



LISTED
FILL, VOID, OR
CAVITY MATERIALS
90G9

Important Notice to User:

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M Fire Protection Product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Please recycle. Printed in U.S.A.
© 3M 2010. All rights reserved.
98-0213-4608-9

3M is a trademark of 3M company.
All other trademarks are the property
of their respective owners.